



## Mekiro B.V.

Tower Building, 22 Water Street  
LIVERPOOL, L3 1BL, UK

Chamber of Commerce – The Hague 27353147

Tel: ++44 151 236 3191 Fax: ++44 151 236 4431, ++44 151 227 1438 e-mail: [quality@mekiro.eu](mailto:quality@mekiro.eu)

### PRODUCT SPECIFICATION

<b>Description:</b>	<b>Base Oil 100 SN</b>	<b>Issue:</b>	<b>1</b>
		<b>100 SN</b>	

### Typical Physical Characteristics

<u>Property</u>	<u>Test</u>	<u>Units</u>	<u>Specification</u>	<u>Typical</u>
Appearance at 20 °C	Visual		Clear and bright	Clear and bright
ASTM Colour	ASTM D6045		1.0 max	0.6
Flash Point, COC	ISO 2592	°C	190 min	207
Kinematic Viscosity, 40 °C	ISO 3104	cSt	18.0 – 23.0	20.4
Kinematic Viscosity, 100 °C	ISO 3104	cSt	-	4.1
NOACK Volatility	CEC-0-93-2008	Wt %	30.0 max	27.0
Density at 15°C	ASTM D1298	kg/l	0.855 – 0.875	0.866
Pour Point	D 5950-02	°C	-12 max	-13
Viscosity Index	D 2270-04	-	95 min	96

NB: This document nullifies and replaces all previous documents referring to this product.